

# JET-LUBE® SEAL-GUARD™

## PREMIUM THREAD COMPOUND

### DESCRIPTION

**JET-LUBE® SEAL-GUARD™** represents the next generation in thread compound technology and design. Just as oilfield pipe materials and connections are engineered for specific applications and field service requirements, so must thread compounds be formulated to meet critical performance requirements. The thread compound must be tailored to the connection design, material (alloy), operating conditions and environmental and occupational health restrictions.

**JET-LUBE SEAL-GUARD** has been specifically formulated to meet the performance requirements of proprietary, metal-to-metal seal and high-interference connection designs utilizing today's high-performance materials, which include "super" chrome and high-alloy steels. The smaller particle size distribution may not provide optimum sealability on 8-round and buttress thread forms.

**JET-LUBE SEAL-GUARD's** advanced base grease and additive technology (**CZ-EX® PLUS**) is further enhanced with high and low-strength polymers and innovative solid lubricants. The result is superior lubrication under high loads with galling resistance equivalent to heavy metal-based compounds in a totally metal-free formulation. This cutting-edge technology provides a high affinity to metal surfaces with a relatively low added-solids content. In addition, there is a large percentage of submicron particles formed by chemical reaction creating a film that gives consistent frictional performance without restricting proper engagement of the connection contact surfaces regardless of connection design.

- Metal free
- Frictional properties consistent with API MODIFIED
- High film strength to protect against galling
- Low solids content to accommodate premium connection design requirements
- Ideal for use on high-chrome connections
- H<sub>2</sub>S Inhibited
- Sticks to wet or oily threads
- Excellent for use on nuts, bolts, or other threaded fasteners

### APPLICATIONS

**JET-LUBE SEAL-GUARD** is recommended for use on premium connections, flow lines, nuts, bolts, etc. Can also be utilized on jacking systems.

## CORPORATE LOCATIONS

Houston, Texas—World Headquarters

Maidenhead, England

Edmonton, Canada

JET-LUBE, INC.  
4849 HOMESTEAD RD.,  
P.O. BOX 21258 (77226-1258)  
HOUSTON, TX 77028

WATS: 800-538-5823  
PHONE: 713-674-7617  
FAX: 713-678-4604  
E-MAIL: [sales@jetlube.com](mailto:sales@jetlube.com)  
[www.jetlube.com](http://www.jetlube.com)

### PRODUCT CHARACTERISTICS

Thickener	Complex Thickeners
Fluid Type	Petroleum (std grade)
Dropping Point (ASTM D-566)	>450°F (232°C)
Specific Gravity	1.22
Density (lb/gal)	10.2
Penetration @77°F (ASTM D-217)	325 - 345
4-Ball (ASTM D-2596) Weld Point, kgf	≥620
Flash Point (ASTM D-92)	>450°F (232°C)
Std Grade Service Range	-20°F (-29°C) to 500°F (260°C)
Friction Factor	1.0

**SEAL-GUARD** has been tested for California Code of Regulations - Title 22, Chapter 30, Article II and is not classified as a hazardous waste. **SEAL-GUARD** is nontoxic, even in a marine environment, as evidenced by test results on the California Hazardous Waste Assessment Bioassay and its "D" rating in the North Sea (OSPAR) Guidelines.

### PACKAGING

Code No.	Container Size	Container
14423	9 lb.	Pail
14412	18 lb.	Pail
14415	45 lb.	Pail
14417	45 lb.	Metal Pail
14424	135 lb.	Drum
14429	450 lb.	Drum

### LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

OILFIELD

OILFIELD

OILFIELD

OILFIELD

OILFIELD

# JET-LUBE, INC.

## MATERIAL SAFETY DATA SHEET

**Product Name:** JET-LUBE® SEAL-GUARD™  
**Chemical Family:** Complex grease base  
**Use:** Thread lubricant and sealant, anti-seize compound

**Manufacturer/Supplier:** JET-LUBE, INC.  
**Address:** 4849 Homestead Rd., Ste. #200  
 Houston, TX, 77028 USA **Phone:** 713-674-7617  
**Emergency Phone:** 713-674-7617 **Fax:** 713-678-4604  
**Chemtrec 24 hours (USA):** 800-424-9300

Hazardous Components	CAS No.	Wt%	OSHA PEL	ACGIH TLV	Other Limits of Exposure
Lubricating Grease	74869219	45-50	Oil mist	N/A	N/A
Nonhazardous Blend	7782425/9002840 7789755/65996614 7440440	40-60			

**Main Hazards—Health Effects**

**Eyes:** May cause irritation. **Inhalation:** Viscous nature may block breathing passages if inhaled. **Ingestion:** May cause diarrhea.  
**Skin:** For hypersensitive persons, may irritate the skin after prolonged periods of contact.

**Eyes:** Flush with water until all residual material is gone. If irritation persists, seek medical help. **Inhalation:** Clear air passage. If respiratory difficulty continues, seek medical help. **Ingestion:** Wash out mouth immediately. Consult physician. **Skin:** Wash thoroughly with hand cleanser, followed by soap & water. Contaminated clothing should be dry cleaned before reuse.

**Extinguishing Media:** Foam, dry powder, Halon®, carbon dioxide, sand, earth & water mist. **Unsuitable Extinguishing Media:** Water jet.  
**Protective Equipment for Fire fighting:** Self-contained breathing apparatus.

**Personal Precautions:** Wear gloves & protective overalls. **Environmental Precautions:** Do not allow it to enter drains. **Spillage:** Scrape up bulk, then wipe up remainder with cloth. To prevent walking hazard, pick up remaining residue with diatomaceous earth.

**Handling:** No special handling precautions necessary. **Storage:** Do not store at elevated temperatures.

**Respiratory Protection:** None needed. **Hand Protection:** Protective gloves for hypersensitive persons.  
**Eye Protection:** Glasses, if applied to parts in motion. **Body Protection:** Overalls.

**Physical State:** Semi-solid paste **Color:** Black **Odor:** Petroleum **pH:** Neutral **Boiling Range/Point °F (°C):** UN  
**Melting Point °F (°C):** >400 (204) **Flash Point (COC) °F (°C):** >430 (221) **Autoignition Temperature °F (°C):** >500 (260)  
**Explosive Properties:** LEL: 0.9% UEL: 7% **Evaporation Rate (Butyl Acetate):** <0.01 **Partition Coefficient (Log Pow):** N/A  
**Vapor Pressure (kPa):** <0.01 **Percent Volatiles:** Nil **Density (g/cm³):** 1.22 **Flammability:** Not flammable at ambient temperature.  
**OAR Value:** N/A **Oxidizing Properties:** None **Water Solubility:** Nil **Vapor Density:** >5

**Stability:** Chemically stable under normal conditions. No photoreactive agents. **Conditions to Avoid:** Powerful sources of ignition & extreme temps. **Materials to Avoid:** Strong inorganic & organic acids, oxidizing agents. **Hazardous Decomposition Products:** Burning generates smoke, airborne soot, hydrocarbons & oxides of carbon, sulfur & nitrogen. Residue mainly comprised of soot & mineral oxides.

**Acute Toxicity:** Not known. **Irritancy—Skin:** Very mild. **Skin Sensitization:** Not known. **Subacute/Sub-chronic Toxicity:** Not known.  
**Genotoxicity:** None known. **Chronic Toxicity:** None known. **California Prop 65:** N/A **Carcinogen:** NTP: No IARC: No **OSHA:** No  
**EC Classification (67/548/EEC):** No **Allergens:** None known. **LC-50:** >4000mg/kg—extrapolated from component data. **LD-50:** N/A

**Possible Effects:** None


**Behavior:** Relatively well behaved. Bioaccumulation potential nil.  
**Environmental Fate:** Highly unlikely to cause notable contamination. Nontoxic to marine or land organisms.

**Product Disposal:** Do not incinerate. Contact waste disposal company or local authority for advice.  
**Container Disposal:** Pails without liner—see Product Disposal section above. Pails with plastic liner—pail may only be disposed of via standard waste disposal services, recycled or reused. Liner—see Product Disposal section above.

Not classified as hazardous for transport. **D.O.T.:** Nonhazardous **UN No.:** Nonhazardous **Air Transport (ICAO & IATA):** Nonhazardous  
**Sea Transport (IMO & IMDG):** Nonhazardous **Road & Rail Transport (ADR/RID):** Nonhazardous

**Labeling Information:** None needed **EC Annex 1 Classification:** Not Applicable. **R Phrases:** R22—harmful if swallowed.  
**S Phrases:** None applicable, as known. **Ozone Depleting Chemicals:** Not applicable. **TSCA:** All components are listed.  
**WHMIS (Canada):** Not controlled. **Canadian DSL:** All components listed. **40 CFR Part 372 (SARA Section 313):** N/A  
**CERCLA:** Nonhazardous **RCRA Hazard Class:** Nonhazardous **SARA 311/312:** None **TSCA 12B Components:** None

SDS first issued. SDS data revised. **New Jersey Right To Know:** See Section II

**Signature:**   
**Prepared by:** Donald A. Oldiges  
**Date Issued:** February 26, 2009

As of issue date, the information contained herein is accurate and reliable to the best of JET-LUBE'S knowledge. JET-LUBE® does not warrant or guarantee its accuracy or reliability and shall not be liable for any loss or damage arising out of the use thereof. It is the user's responsibility to satisfy itself that the information offered for its consideration is suitable for its particular use.

LEGEND	
I.	IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY
II.	COMPOSITION INFORMATION ON INGREDIENTS
III.	HAZARDS IDENTIFICATION
IV.	FIRST AID MEASURES
V.	FIRE FIGHTING MEASURES
VI.	ACCIDENTAL RELEASE MEASURES
VII.	HANDLING AND STORAGE
VIII.	EXPOSURE CONTROL/PERSONAL PROTECTION
IX.	PHYSICAL AND CHEMICAL PROPERTIES
X.	STABILITY AND REACTIVITY
XI.	TOXICOLOGICAL INFORMATION
XII.	ECOLOGICAL INFORMATION
XIII.	WASTE DISPOSAL
XIV.	TRANSPORT INFORMATION
XV.	REGULATORY INFORMATION
XVI.	OTHER INFORMATION

**HMIS SYMBOL**

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PPI	B

**NFPA SYMBOL**

