



RUST-GUARD®

AEROSOL GRADE CORROSION INHIBITOR

DESCRIPTION

RUST-GUARD is a water displacing specialised formula which dries to a uniform, thin wax film to effectively seal out moisture and corrosion. **RUST-GUARD** provides 12-18 months protection on all metal and alloy surfaces, even under harsh environmental conditions such as water, high humidity or salt spray.

RUST-GUARD may be used both indoors and outdoors as a protective coating on raw materials, machined parts, tools, pipe, fittings, valves, etc. while they are being stored or in transit. **RUST-GUARD** will not crack or flake off and, since it is applied in aerosol or liquid form, it penetrates fully into even the smallest crevices to displace moisture and prevent rust and corrosion.

RUST-GUARD is blue in colour to facilitate visual check of product application and is easily and safely removed by use of a safety solvent such as **JET-LUBE CLEAN UP PLUS**.

- Nontoxic
- Economical to use
- Penetrates deeply, displacing moisture
- Prevents rust and corrosion
- Indoor/Outdoor formula
- Will not crack/peel off
- Easily removed
- Visually identifiable colour
- For drill pipe, tubing, casing and line pipe, removal prior to application of running compounds is not necessary
- Conforms to MIL-PRF-16173E Grade I & II

APPLICATIONS

RUST-GUARD may be used to provide long-term protection from rust and corrosion for a variety of Industrial, Marine, Aviation and Oilfield duties. May be diluted with 10-20% White Spirit to produce desired viscosity.

PRODUCT CHARACTERISTICS

Service range	-30°C to 138°C (-22 to 280°F)
Film Material	Calcium Soap Wax
Fluid Type	Petroleum
Colour/Appearance	Blue-green
Specific Gravity	0.85
Flash Point (ASTM D-1310) T.O.C.	>38°C (100°F)
Wt.% Non-Volatiles (ASTM D-1644)	30 Typical
Film Thickness (TYPICAL)	0.025 mm
Rust and Corrosion Resistance	
Copper Strip Corrosion (ASTM D-130)	1B Max
Salt Fog Resistance (ASTM B-117)	No Rust>20 days
Underwater Submission	No Rust>30 days
Humidity Resistance	No Rust>30 days
Shelf-life	5 years

COVERAGE INFORMATION

The coverage area provided by **RUST-GUARD** will vary with film thickness, surface finish and loss or spillage. Typical results that may be expected:

22m² - 44m²/litre
8 – 12m²/ aerosol can

PACKAGING

Code No.	Size	Container
JA13240	12 x 400ml	Aerosol can
JA13237	12 x 500ml	Trigger spray
JA13234	5 litre	Can
JA13236	25 litre	Poly Can
JA13229	189 litre	Barrel

LIMITED WARRANTY

Jet-Lube (UK) Limited makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube (UK) Limited materials and workmanship.

This limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube (UK) Limited.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube (UK) Limited shall not be liable for incidental or consequential damages

Sept 2014